



Modelis
Spring-loaded diaphragm (NBR); Spring-loaded piston; (10 to 70 bar versions)
Pieteikums platība
Air, hydraulic oil, oil emulsions, water
Vides temperatūra
-25 °C to +85 °C
Elektriskais pieslēgums
Tab connectors 2 x 6.3 x 0.8
Slēgšanas biežums
200/min.
Slēgšanas spriegums
42 V
Materiāls
Galvanised steel

Apraksts

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Funkcija | Iestatišanas diapazons |
|----------------|--------|----------|------------------------|
| K- 07 30 24 94 | G 1/8 | closer | 0,3 - 2,0 bar |
| K- 07 30 24 95 | G 1/8 | closer | 1,0 - 10,0 bar |
| K- 07 30 24 96 | G 1/8 | closer | 10,0 - 70,0 bar |
| K- 07 30 24 97 | G 1/4 | closer | 0,3 - 2,0 bar |
| K- 07 30 24 98 | G 1/4 | closer | 1,0 - 10,0 bar |
| K- 07 30 24 99 | G 1/4 | closer | 10,0 - 70,0 bar |
| K- 07 30 24 10 | G 1/8 | opener | 0,3 - 2,0 bar |
| K- 07 30 24 11 | G 1/8 | opener | 1,0 - 10,0 bar |
| K- 07 30 24 12 | G 1/8 | opener | 10,0 - 70,0 bar |
| K- 07 30 24 13 | G 1/4 | opener | 0,3 - 2,0 bar |
| K- 07 30 24 14 | G 1/4 | opener | 1,0 - 10,0 bar |
| K- 07 30 24 15 | G 1/4 | opener | 10,0 - 70,0 bar |