



Modelis  
Spring-loaded diaphragm (UR); Spring-loaded piston; (10 to 70 bar versions)  
Vides temperatūra  
-25 °C to +85 °C  
Elektriskais pieslēgums  
Bayonet coupling connector Ø 2.5 mm  
Slēgšanas biežums  
200/min.  
Funkcija  
Changeover  
Mērišanas spriegums  
42 V  
Materiāls  
Galvanised steel

## Apraksts

Special pressure switches for critical (water) or outdoor applications. Maximum degree of protection IP67 when a bayonet coupling is used for the electrical connection.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Mērišanas spriegums<br>V | Vītnes | Iestatišanas diapazons |
|----------------|--------------------------|--------|------------------------|
| K- 07 30 28 36 | 42                       | G 1/8  | 0,5 - 2,0 bar          |
| K- 07 30 28 37 | 42                       | G 1/8  | 1,0 - 10,0 bar         |
| K- 07 30 28 38 | 42                       | G 1/8  | 10,0 - 70,0 bar        |
| K- 07 30 28 39 | 42                       | G 1/4  | 0,5 - 2,0 bar          |
| K- 07 30 28 40 | 42                       | G 1/4  | 1,0 - 10,0 bar         |
| K- 07 30 28 41 | 42                       | G 1/4  | 10,0 - 70,0 bar        |