

# K-DRS W WECHSELKONTAKT ANFLANSCHBAR

Pressure switches changeover type, flange mounting



Modelis  
Spring-loaded diaphragm (NBR)  
Pieteikums platība  
Air, neutral gases (lubricated or unlubricated)  
Vides temperatūra  
-25 °C to +85 °C  
Elektriskais pieslēgums  
Coupling plug PG 11 P nach ISO 4400  
Slēgšanas biežums  
60/min.  
Slēgšanas spriegums  
max. 250 V AC/DC  
Funkcija  
Changeover  
Materiāls  
to 10 bar: plastic Grivory (PA 61/XT) bzw.; to 16 bar: Alu black eloxed

## Apraksts

Special pressure switches for pneumatic applications. Extremely precise thanks to the large control diaphragm. Two through holes in the housing for flanging the switch.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | Iestatišanas diapazons |
|----------------|--------|------------------------|
| K- 07 30 28 42 | G 1/4  | 0,2 - 6,0 bar          |
| K- 07 30 28 43 | G 1/4  | 0,5 - 10,0 bar         |
| K- 07 30 28 44 | G 1/4  | 0,5 - 16,0 bar         |