



Darba frekvence

40 kHz \pm 2 kHz

Savienojums

4-pin connection for headphones and charger, 3.5 mm stereo jack for connecting sensor and cable

Lāzers

Wave length: 655 to 660 nm, Output power: 0.4 to 0.5 mW

Energoapgāde

Internal NiMH rechargeable battery

Ekspluatācijas ilgums

Approx. 6 hours without laser / 4 hours with laser

Uzlādes ilgums

Approx. 1.5 hours

Gultņa temperatūra

-10 °C to +50 °C

Izmantošanas temperatūra

0 °C to +40 °C

Apraksts

Function: The annual energy cost of leaks in pneumatic and gas systems are high and avoidable. When these gases flow unused out of leaks, they create noises inaudible to the human ear. With the LS 100, even the smallest leaks can be heard from several metres distance. It transforms inaudible signals to a frequency that can be detected visually on the display and acoustically with the supplied sound-proof headphones. Use: leakage inspections of pneumatic, gas, steam and vacuum systems.
The advantages of the LS 100: Simple and quick measurement, even from distances of several metres. Measurements can be taken on running systems, without affecting their operation.

The device is quickly amortised by the high cost savings

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums

Apraksts

K- 07 25 19 53 Leak detection device, including accessories in a practical carrying case