

K-DIFFERENZDRUCKMANO Z

Differential pressure gauges with parallel male connector



Tips

711.12

Modelis

Bourdon-tube pressure gauge with parallel male connector and two separate measuring systems

Izmantošana

to measure differential pressures or two different pressures

For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise

Kvalitātes klase

1,6

Vides temperatūra

no -20 °C līdz +60 °C

Vielas temperatūra

maks. +60 °C

Korpuss, gredzens

Steel, black

Mērelementa un rādītāja materiāls

Vara sakausējums

Skatstikls

Flat instrument glass

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Mērišanas diapazons	Ø mm	Savienojums
K- 07 20 00 55	0 - 1.0 bar	100.0	G 1/2"
K- 07 20 00 56	0 - 1.6 bar	100.0	G 1/2"
K- 07 20 00 57	0 - 2.5 bar	100.0	G 1/2"
K- 07 20 00 58	0 - 4.0 bar	100.0	G 1/2"
K- 07 20 00 59	0 - 6.0 bar	100.0	G 1/2"
K- 07 20 00 60	0 - 10.0 bar	100.0	G 1/2"