

Diaphragm pressure gauges for chemical applications, connection radial on bottom

**Tips**

422.12 (robust), 432.50 (chemical)

Modelis

Diaphragm pressure gauge in robust design or for chemical applications

Izmantošanaat chemical applications in aggressive environments
for gaseous or liquid media,**Kvalitātes klase**

1,6

Vides temperatūra

no -20 °C līdz +60 °C

Vielas temperatūra

max. +100 °C

Korpuss, gredzens

Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications)

Mērelements

CrNi steel

Rādītāja mehānisms

Copper alloy (robust type), CrNi steel (type for chemical applications)

Skatstikls

Flat instrument glass (robust type), Laminated safety glass (type for chemical applications)

Ø mērišanas atloks

100 mm

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Ø mērišanas atloks mm | Mērišanas diapazons | Ø mm | Savienojums |
|----------------|--------------------------|---------------------|---------|-------------|
| K- 07 20 10 25 | 100 | 0 - 6.0 bar | 100.0 | G 1/2" |
| K- 07 20 10 26 | 100 | 0 - 10.0 bar | 100.0 | G 1/2" |