



Tips

111.10 (radial connector on bottom)

Modelis

Bourdon-tube pressure gauge in standard design

Izmantošana

gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise

Kvalitātes klase

1.6 (Art No. K-07200303, K-07403298 - K-07201188: 2.5)

Rādītājs

Red pointer to the window (for Ø 160 mm - red pointer on the scale). For measuring ranges 0...0,6 bar bis 0...60 bar

Vides temperatūra

no -20 °C līdz +60 °C

Vielas temperatūra

maks. +60 °C

Korpuss

Plastic

Mērelementa un rādītāja materiāls

Vara sakausējums

Skatstikls

Transparent plastic

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Mērīšanas diapazons	Ø mm	Savienojums
K- 07 20 03 03	-1200 / 0.0 mbar	100.0	G 1/2"
K- 07 20 03 04	-1 / 0.0 bar	100.0	G 1/2"
K- 07 20 03 05	-1 / +0.6 bar	100.0	G 1/2"
K- 07 20 03 06	-1 / +1.5 bar	100.0	G 1/2"
K- 07 20 03 07	-1 / +3.0 bar	100.0	G 1/2"
K- 07 20 03 08	-1 / +5.0 bar	100.0	G 1/2"
K- 07 20 03 09	-1 / +9.0 bar	100.0	G 1/2"
K- 07 20 02 84	0 - 0.6 bar	100.0	G 1/2"
K- 07 20 02 85	0 - 1.0 bar	100.0	G 1/2"
K- 07 20 02 86	0 - 1.6 bar	100.0	G 1/2"
K- 07 20 02 87	0 - 2.5 bar	100.0	G 1/2"
K- 07 20 02 88	0 - 4.0 bar	100.0	G 1/2"
K- 07 20 02 89	0 - 6.0 bar	100.0	G 1/2"
K- 07 20 02 90	0 - 10.0 bar	100.0	G 1/2"
K- 07 20 02 91	0 - 16.0 bar	100.0	G 1/2"
K- 07 20 02 92	0 - 25.0 bar	100.0	G 1/2"
K- 07 20 02 93	0 - 40.0 bar	100.0	G 1/2"
K- 07 20 11 86	0 - 60.0 bar	100.0	G 1/2"
K- 07 20 11 87	0 - 100.0 bar	100.0	G 1/2"
K- 07 20 11 88	0 - 160.0 bar	100.0	G 1/2"