

Glycerine-filled pressure gauges Glycerine-filled pressure gauges, CrNi steel type



Tips

233.50

Izmantošana

For gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere

Modelis

Glycerine-filled bourdon-tube pressure gauge, CrNi steel type

Kvalitātes klase

1.6 (Ø 63 mm), 1.0 (Ø 100 mm and Ø 160 mm)

Vides temperatūra

no -20 °C līdz +60 °C

Vielas temperatūra

max. +100 °C

Korpuss

CrNi steel

Skatstikls

Laminated safety glass Ø 63 = Polycarbonate

Apraksts

For use in the chemical/petrochemical process industry, power stations, machinery and industrial plant engineering. For measuring points with high dynamic pressure loads and vibrations.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Mērišanas diapazons	Ø mm	Savienojums
K- 07 20 11 93	-1 / 0.0 bar	63.0	G 1/4"
K- 07 20 11 95	-1 / +0.6 bar	63.0	G 1/4"
K- 07 20 11 97	-1 / +1.5 bar	63.0	G 1/4"
K- 07 20 11 99	-1 / +3.0 bar	63.0	G 1/4"
K- 07 20 12 01	-1 / +5.0 bar	63.0	G 1/4"
K- 07 20 12 03	-1 / +9.0 bar	63.0	G 1/4"
K- 07 20 12 05	-1 / +15.0 bar	63.0	G 1/4"
K- 07 20 12 08	0 - 1.0 bar	63.0	G 1/4"
K- 07 20 12 10	0 - 1.6 bar	63.0	G 1/4"
K- 07 20 12 12	0 - 2.5 bar	63.0	G 1/4"
K- 07 20 12 14	0 - 4.0 bar	63.0	G 1/4"
K- 07 20 12 16	0 - 6.0 bar	63.0	G 1/4"
K- 07 20 12 18	0 - 10.0 bar	63.0	G 1/4"
K- 07 20 12 20	0 - 16.0 bar	63.0	G 1/4"
K- 07 20 12 22	0 - 25.0 bar	63.0	G 1/4"
K- 07 20 12 24	0 - 40.0 bar	63.0	G 1/4"
K- 07 20 12 26	0 - 60.0 bar	63.0	G 1/4"
K- 07 20 12 28	0 - 100.0 bar	63.0	G 1/4"
K- 07 20 12 30	0 - 160.0 bar	63.0	G 1/4"
K- 07 20 12 32	0 - 250.0 bar	63.0	G 1/4"
K- 07 20 12 34	0 - 400.0 bar	63.0	G 1/4"
K- 07 20 12 36	0 - 600.0 bar	63.0	G 1/4"
K- 07 20 11 92	-1 / 0.0 bar	100.0	G 1/2"
K- 07 20 11 94	-1 / +0.6 bar	100.0	G 1/2"
K- 07 20 11 96	-1 / +1.5 bar	100.0	G 1/2"
K- 07 20 11 98	-1 / +3.0 bar	100.0	G 1/2"
K- 07 20 12 00	-1 / +5.0 bar	100.0	G 1/2"
K- 07 20 12 02	-1 / +9.0 bar	100.0	G 1/2"
K- 07 20 12 04	-1 / +15.0 bar	100.0	G 1/2"
K- 07 20 12 06	0 - 0.6 bar	100.0	G 1/2"
K- 07 20 12 07	0 - 1.0 bar	100.0	G 1/2"

Apzīmējums	Mērišanas diapazons	Ø mm	Savienojums
K- 07 20 12 09	0 - 1.6 bar	100.0	G 1/2"
K- 07 20 12 11	0 - 2.5 bar	100.0	G 1/2"
K- 07 20 12 13	0 - 4.0 bar	100.0	G 1/2"
K- 07 20 12 15	0 - 6.0 bar	100.0	G 1/2"
K- 07 20 12 17	0 - 10.0 bar	100.0	G 1/2"
K- 07 20 12 19	0 - 16.0 bar	100.0	G 1/2"
K- 07 20 12 21	0 - 25.0 bar	100.0	G 1/2"
K- 07 20 12 23	0 - 40.0 bar	100.0	G 1/2"
K- 07 20 12 25	0 - 60.0 bar	100.0	G 1/2"
K- 07 20 12 27	0 - 100.0 bar	100.0	G 1/2"
K- 07 20 12 29	0 - 160.0 bar	100.0	G 1/2"
K- 07 20 12 31	0 - 250.0 bar	100.0	G 1/2"
K- 07 20 12 33	0 - 400.0 bar	100.0	G 1/2"
K- 07 20 12 35	0 - 600.0 bar	100.0	G 1/2"
K- 07 20 03 48	0 - 0.6 bar	160.0	G 1/2"
K- 07 20 03 49	0 - 1.0 bar	160.0	G 1/2"
K- 07 20 03 50	0 - 1.6 bar	160.0	G 1/2"
K- 07 20 03 51	0 - 2.5 bar	160.0	G 1/2"
K- 07 20 03 52	0 - 4.0 bar	160.0	G 1/2"
K- 07 20 03 53	0 - 6.0 bar	160.0	G 1/2"
K- 07 20 03 54	0 - 10.0 bar	160.0	G 1/2"
K- 07 20 03 55	0 - 16.0 bar	160.0	G 1/2"
K- 07 20 03 56	0 - 25.0 bar	160.0	G 1/2"
K- 07 20 03 57	0 - 40.0 bar	160.0	G 1/2"
K- 07 20 03 58	0 - 60.0 bar	160.0	G 1/2"
K- 07 20 03 59	0 - 100.0 bar	160.0	G 1/2"
K- 07 20 03 60	0 - 160.0 bar	160.0	G 1/2"
K- 07 20 03 61	0 - 250.0 bar	160.0	G 1/2"
K- 07 20 03 62	0 - 400.0 bar	160.0	G 1/2"
K- 07 20 03 63	0 - 600.0 bar	160.0	G 1/2"