



Tips

233.30

Izmantošana

For gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere

Modelis

Glycerine-filled Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)

Kvalitātes klase

1,6 (Ø 63 mm), 1,0 (Ø 100 mm)

Vides temperatūra

no -20 °C līdz +60 °C

Vielas temperatūra

max. +100 °C

Korpuss

CrNi steel

Skatstikls

Laminated safety glass Ø 63 = Polycarbonate

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Mērišanas diapazons	Ø mm	Savienojums
K- 07 20 07 03	-1 / 0.0 bar	63.0	G 1/4"
K- 07 20 07 04	0 - 4.0 bar	63.0	G 1/4"
K- 07 20 07 05	0 - 6.0 bar	63.0	G 1/4"
K- 07 20 07 06	0 - 10.0 bar	63.0	G 1/4"
K- 07 20 07 07	0 - 16.0 bar	63.0	G 1/4"
K- 07 20 07 08	0 - 25.0 bar	63.0	G 1/4"
K- 07 20 07 09	0 - 40.0 bar	63.0	G 1/4"
K- 07 20 07 10	0 - 60.0 bar	63.0	G 1/4"
K- 07 20 07 11	0 - 100.0 bar	63.0	G 1/4"
K- 07 20 07 12	0 - 160.0 bar	63.0	G 1/4"
K- 07 20 07 13	0 - 250.0 bar	63.0	G 1/4"
K- 07 20 07 14	0 - 400.0 bar	63.0	G 1/4"
K- 07 20 01 79	-1 / 0.0 bar	100.0	G 1/2"
K- 07 20 01 80	-1 / +1.5 bar	100.0	G 1/2"
K- 07 20 01 81	-1 / +3.0 bar	100.0	G 1/2"
K- 07 20 01 82	-1 / +5.0 bar	100.0	G 1/2"
K- 07 20 01 83	-1 / +9.0 bar	100.0	G 1/2"
K- 07 20 01 84	0 - 2.5 bar	100.0	G 1/2"
K- 07 20 01 85	0 - 4.0 bar	100.0	G 1/2"
K- 07 20 01 86	0 - 6.0 bar	100.0	G 1/2"
K- 07 20 01 87	0 - 10.0 bar	100.0	G 1/2"
K- 07 20 01 88	0 - 16.0 bar	100.0	G 1/2"
K- 07 20 01 89	0 - 25.0 bar	100.0	G 1/2"
K- 07 20 01 90	0 - 40.0 bar	100.0	G 1/2"
K- 07 20 01 91	0 - 60.0 bar	100.0	G 1/2"
K- 07 20 01 92	0 - 100.0 bar	100.0	G 1/2"
K- 07 20 01 93	0 - 160.0 bar	100.0	G 1/2"
K- 07 20 01 94	0 - 250.0 bar	100.0	G 1/2"
K- 07 20 01 95	0 - 400.0 bar	100.0	G 1/2"
K- 07 20 01 96	0 - 600.0 bar	100.0	G 1/2"