

# K-KFMM H MBAR

Capsule-type pressure gauges, connection on rear



## Tips

611.10 (Ø 63), 612.20 (Ø 100)

## Izmantošana

For gaseous, dry, non-corrosive media

## Modelis

Capsule-type pressure gauge

## Kvalitātes klase

1,6

## Vides temperatūra

no -20 °C līdz +60 °C

## Vielas temperatūra

max. +100 °C; max. +80 °C (at type Ø 100 mm, rear connector excentric)

## Korpuss

Steel, black (Ø 63 mm)CrNi steel (Ø 100 mm)

## Mērelementa un rādītāja materiāls

Vara sakausējums

## Skatstikls

Plexiglass (Ø 63 mm), flat instrument glass (Ø 100 mm)

## Apraksts

With zero correction

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Mērišanas diapazons	Ø mm	Savienojums
K- 07 20 06 97	0 - 40 mbar	63.0	G 1/4"
K- 07 20 06 98	0 - 60 mbar	63.0	G 1/4"
K- 07 20 06 99	0 - 100 mbar	63.0	G 1/4"
K- 07 20 07 00	0 - 160 mbar	63.0	G 1/4"
K- 07 20 07 01	0 - 250 mbar	63.0	G 1/4"
K- 07 20 07 02	0 - 400 mbar	63.0	G 1/4"
K- 07 20 01 25	0 - 25 mbar	100.0	G 1/2"
K- 07 20 01 26	0 - 40 mbar	100.0	G 1/2"
K- 07 20 01 27	0 - 60 mbar	100.0	G 1/2"
K- 07 20 01 28	0 - 100 mbar	100.0	G 1/2"
K- 07 20 01 29	0 - 160 mbar	100.0	G 1/2"
K- 07 20 01 30	0 - 250 mbar	100.0	G 1/2"
K- 07 20 01 31	0 - 400 mbar	100.0	G 1/2"