

# K-KALIBRIER-TEST UND SERVICE

Calibration, testing and service unit



Modelis  
Calibration, testing and service unit  
Mērišanas vielas temperatūra  
-20 °C to +80 °C  
Precizitāte  
0,25% FS  
Vides temperatūra  
-10 °C to +50 °C  
Daļas, kas saskaras ar mērišanas vielu  
CrNi-steel with NBR seal  
Korpuss  
Die-cast zinc

## Apraksts

Service case for quick and precise pressure gauge calibration. Suitable for service and maintenance providers of all kinds as well as instrumentation control workshops and quality assurance. Simple operation using four buttons. The high sampling rate (100 measurements / second) guarantees an accurate analysis at the measuring point. Comprised of a CPG500 digital gauge and a CPP40 pneumatic hand test pump with a connecting cable for pressure generation. Operating manual, calibration certificate 3.1, two AA batteries and a protective rubber cap for the housing are enclosed. Includes a plastic emergency case with foam padding.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Mērišanas diapazons | Savienojums |
|----------------|---------------------|-------------|
| K- 07 20 12 70 | -0.95 / +40 bar     | G 1/4"      |