



Modelis
 Konstants sūknis
 Eļļas noplūdes savienojums G 3/8"
 Viton blīvējumi
 Vītne iesūkšanas pusē
 G 1" for VFU 5 ccm
 G 3/4" for VFU 12 - 56 ccm
 G 1" from VFU 63 ccm
 Vītne spiediena pusē
 G 1" for VFU 5 ccm
 G 3/4" for VFU 12 - 56 ccm
 G 1" from VFU 63 ccm
 Piegādes apjoms
 ar iesūcējiemavām un pārbaudes šļūteni

Apraksts

Fixed displacement pump – hole pattern 80 x 80 – dia. 80 – shaft 8x32x16 ISO 14 – threaded fitting

Suction socket Ø 51.8 mm for HK PBA *** 51SF,

Suction socket Ø 64.5 mm for HK PBA *** 64SF

Changing rotational direction can be done by changing the setting screw and suction socket. Details can be found in the accompanying instructions.

Produkts

Apzīmējums	VFU cm ³	p2maks. bar	p3maks. bar	Apgriezienu skaits maks. r/min	Apgriezienu skaitsmin. r/min	A mm	B mm	C mm	D mm	Griešanās virziens	E mm
HK PBA 005 L 80 51 SF	5	350	400	3300	500	195	104	76	108	Pa kreisi	54
HK PBA 012 L 80 51 SF	12	350	400	3100	500	195	104	76	108	Pa kreisi	54
HK PBA 018 L 80 51 SF	18	350	400	2900	500	195	104	76	108	Pa kreisi	54
HK PBA 025 L 80 51 SF	25	350	400	2700	500	195	104	76	108	Pa kreisi	54
HK PBA 032 L 80 51 SF	32	350	400	2700	500	202	108	82	108	Pa kreisi	54
HK PBA 040 L 80 51 SF	40	350	400	2500	500	202	108	82	108	Pa kreisi	54
HK PBA 050 L 80 51 SF	50	350	400	2500	500	215	118	94	108	Pa kreisi	54
HK PBA 056 L 80 51 SF	56	350	400	2300	500	215	118	94	108	Pa kreisi	54
HK PBA 063 L 80 51 SF	63	350	400	2300	500	215	118	94	108	Pa kreisi	54
HK PBA 080 L 80 51 SF	80	350	400	2100	500	242	132	104	122	Pa kreisi	60
HK PBA 080 L 80 64 SF	80	350	400	2100	500	242	132	104	122	Pa kreisi	60
HK PBA 108 L 80 51 SF	108	350	400	1900	500	242	132	105	122	Pa kreisi	60
HK PBA 108 L 80 64 SF	108	350	400	1900	500	242	132	105	122	Pa kreisi	60
HK PBA 130 LR 80 51 SF	130	350	400	1750	500	242	132	105	122	Reversīvs	60
HK PBA 130 LR 80 64 SF	130	350	400	1750	500	242	132	105	122	Reversīvs	60

p2 = darba spiediens

p3 = augstākais spiediens