



Caurules garums

3 m

Ekspluatācijas temperatūra

-60 °C to +100 °C (PA 12)

Iepakojuma vienība

20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!

Īpašības

Resistant to corrosion, vibration, impact, ageing, high pressures and heat

Materiāls

Polyamid PA 12, hard (according to DIN 73378)

## Apraksts

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Caurules iekšējais Ø mm	Caurules ārējais Ø mm	maks. ekspluatācijas spiediens pie 20 °C bar	Krāsa
K- 07 10 04 56 9	12	12	38	zils
K- 07 10 04 58 9	12	12	38	melns
K- 07 10 04 60 12	15	15	25	zils
K- 07 10 04 62 12	15	15	25	melns
K- 07 10 04 64 14	18	18	28	zils
K- 07 10 04 66 14	18	18	28	melns
K- 07 10 04 68 18	22	22	22	zils
K- 07 10 04 70 18	22	22	22	melns
K- 07 10 04 72 23	28	28	20	zils
K- 07 10 04 74 23	28	28	20	melns