

# K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

**HANSA FLEX**

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Caurules garums

3 m

Ekspluatācijas temperatūra

-60 °C to +100 °C (PA 12)

Iepakojuma vienība

10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units!

Īpašības

Resistant to corrosion, vibration, impact, ageing, high pressures and heat

Materiāls

Polyamid PA 12, hard (according to DIN 73378)

## Apraksts

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Caurules iekšējais Ø mm	Caurules ārējais Ø mm	maks. ekspluatācijas spiediens pie 20 °C bar	Krāsa
K- 07 10 04 57	9	12	38	zils
K- 07 10 04 59	9	12	38	melns
K- 07 10 04 61	12	15	25	zils
K- 07 10 04 63	12	15	25	melns
K- 07 10 04 65	14	18	28	zils
K- 07 10 04 67	14	18	28	melns
K- 07 10 04 69	18	22	22	zils
K- 07 10 04 71	18	22	22	melns
K- 07 10 04 73	23	28	20	zils
K- 07 10 04 75	23	28	20	melns