

K-SA MUFFE 16

Weld-on sleeve 16 made of black steel ST 37-2, DIN 2986 with continuous thread



Darba spiediens
Max. 50 bar
Pieslēguma vītne
acc. ISO 7-1
Materiāls
black steel ST 37-2

Apraksts

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Garums mm
K- 07 40 35 30	R 1/4	25.0
K- 07 40 35 33	R 3/8	26.0
K- 07 40 35 29	R 1/2	34.0
K- 07 40 35 32	R 3/4	36.0
K- 07 40 35 26	R 1	43.0
K- 07 40 35 28	R 1 1/4	48.0
K- 07 40 35 27	R 1 1/2	48.0
K- 07 40 35 31	R 2	56.0
K- 07 40 50 36	R 2 1/2	65.0
K- 07 40 50 37	R 3	71.0