


K-RED FLANSCH 80-100 IG INFI

Reducing flange Ø 80 mm/Ø 110 mm with female thread



Darba vides
Compressed air, vacuum, inert gases
Eksploatācijas spiediens
-0,99 bar - 15 bar
Temperatūras diapazons
-20 °C to +80 °C
Blīvgredzens
NBR
Drošības gredzens
Technopolymer
Iedobes skrūve
Galvanised steel
Korpuss
Aluminium, treated surface
paškontrējošs uzgrieznis
Galvanised steel
Spīlgredzens
Stainless steel 1.4301
Uzgrieznis
Aluminium, surface treated
Vadgredzens
Technopolymer

Produkts

| Apzīmējums | caurules ārējam Ø mm | Savienojums | A mm | L mm | SW mm |
|----------------|----------------------|-------------|---------|---------|----------|
| K- 07 40 55 23 | 80 | G 3/4" | 14.5 | 42.0 | 42 |
| K- 07 40 55 24 | 80 | G 1" | 17.0 | 42.0 | 49 |
| K- 07 40 55 25 | 80 | G 1 1/2 | 20.0 | 42.0 | 66 |
| K- 07 40 55 26 | 80 | G 2" | 22.0 | 42.0 | 80 |
| K- 07 40 54 73 | 110 | G 3/4" | 14.5 | 48.0 | 42 |
| K- 07 40 54 74 | 110 | G 1" | 17.0 | 48.0 | 49 |
| K- 07 40 54 75 | 110 | G 1 1/2 | 20.0 | 48.0 | 66 |
| K- 07 40 54 76 | 110 | G 2" | 22.0 | 48.0 | 80 |