


# K-RED FLANSCH 80-100 IG INFI

Reducing flange Ø 80 mm/Ø 110 mm with female thread



Darba vides  
Compressed air, vacuum, inert gases  
Eksploatācijas spiediens  
-0,99 bar - 15 bar  
Temperatūras diapazons  
-20 °C to +80 °C  
Blīvgredzens  
NBR  
Drošības gredzens  
Technopolymer  
Iedobes skrūve  
Galvanised steel  
Korpuss  
Aluminium, treated surface  
paškontrējošs uzgrieznis  
Galvanised steel  
Spīlgredzens  
Stainless steel 1.4301  
Uzgrieznis  
Aluminium, surface treated  
Vadgredzens  
Technopolymer

## Produkts

Apzīmējums	caurules ārējam Ø mm	Savienojums	A mm	L mm	SW mm
K- 07 40 55 23	80	G 3/4"	14.5	42.0	42
K- 07 40 55 24	80	G 1"	17.0	42.0	49
K- 07 40 55 25	80	G 1 1/2	20.0	42.0	66
K- 07 40 55 26	80	G 2"	22.0	42.0	80
K- 07 40 54 73	110	G 3/4"	14.5	48.0	42
K- 07 40 54 74	110	G 1"	17.0	48.0	49
K- 07 40 54 75	110	G 1 1/2	20.0	48.0	66
K- 07 40 54 76	110	G 2"	22.0	48.0	80