

# K-T-STECK VB 80-100 INFI

T-push-in connector Ø 80 mm/Ø 110 mm



Darba vides  
Compressed air, vacuum, inert gases  
Eksploatācijas spiediens  
-0,99 bar - 15 bar  
Temperatūras diapazons  
-20 °C to +80 °C  
Blīvgredzens  
NBR  
Drošības gredzens  
Technopolymer  
Iedobes skrūve  
Galvanised steel  
Korpuss  
Aluminium, treated surface  
paškontrējošs uzgrieznis  
Galvanised steel  
Spīlgredzens  
Stainless steel 1.4301  
Uzgrieznis  
Aluminium, surface treated  
Vadgredzens  
Technopolymer

## Produkts

| Apzīmējums     | Caurules ārējais Ø | B<br>mm | C1<br>mm | C2<br>mm | E<br>mm | L1<br>mm | L2<br>mm | SW<br>mm |
|----------------|--------------------|---------|----------|----------|---------|----------|----------|----------|
| K- 07 40 55 16 | 80 - 80 - 80 mm    | 91.0    | 109.0    | 54.5     | 145.0   | 291.5    | 138.0    | 6        |
| K- 07 40 54 67 | 110 - 110 - 110 mm | 125.5   | 150.5    | 75.0     | 200.0   | 401.0    | 200.5    | 8        |