

K-RD MUFFE RUND

Reducing sockets, round



Darba spiediens
Max. 20 bar
Iekšējā vītne
Parallel to DIN EN ISO 228-1
Materiāls
Stainless steel 1.4408

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | L1 mm | Vītne 1 iekšpusē | Vītne 2 iekšpusē |
|----------------|----------|------------------|------------------|
| K- 07 40 14 73 | 27.0 | G 1/4 | G 1/8 |
| K- 07 40 14 74 | 28.4 | G 3/8 | G 1/8 |
| K- 07 40 14 75 | 29.5 | G 3/8 | G 1/4 |
| K- 07 40 45 80 | 32.0 | G 1/2 | G 1/8 |
| K- 07 40 14 76 | 32.0 | G 1/2 | G 1/4 |
| K- 07 40 14 77 | 33.5 | G 1/2 | G 3/8 |
| K- 07 40 14 78 | 36.0 | G 3/4 | G 3/8 |
| K- 07 40 14 79 | 38.5 | G 3/4 | G 1/2 |
| K- 07 40 45 81 | 38.8 | G 1 | G 3/8 |
| K- 07 40 14 80 | 40.5 | G 1 | G 1/2 |
| K- 07 40 14 81 | 41.5 | G 1 | G 3/4 |
| K- 07 40 45 82 | 43.5 | G 1 1/4 | G 1/2 |
| K- 07 40 14 82 | 45.0 | G 1 1/4 | G 3/4 |
| K- 07 40 14 83 | 48.0 | G 1 1/4 | G 1 |
| K- 07 40 45 83 | 47.5 | G 1 1/2 | G 3/4 |
| K- 07 40 14 84 | 54.1 | G 1 1/2 | G 1 |
| K- 07 40 14 85 | 54.0 | G 1 1/2 | G 1 1/4 |
| K- 07 40 14 86 | 54.0 | G 2 | G 1 |
| K- 07 40 45 84 | 57.0 | G 2 | G 1 1/4 |
| K- 07 40 14 87 | 56.0 | G 2 | G 1 1/2 |