

K-XG LOESBAR IG IG FLACHDICHT

Detachable double nipples, female, flat seat



Darba spiediens
Max. 10 bar
Iekšējā vītne
Parallel to DIN EN ISO 228-1
Ārējā vītne
Parallel to DIN EN ISO 228-1
Materiāls
Stainless steel 1.4408

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | SW1 mm | SW2 mm |
|----------------|---------|----------|-----------|-----------|
| K- 07 40 45 85 | G 1/8 | 32.3 | 29 | 18 |
| K- 07 40 45 94 | G 1/4 | 32.4 | 29 | 18 |
| K- 07 40 45 95 | G 3/8 | 34.7 | 34 | 22 |
| K- 07 40 46 00 | G 1/2 | 40.0 | 39 | 26 |
| K- 07 40 46 01 | G 3/4 | 42.0 | 47 | 32 |
| K- 07 40 46 02 | G 1 | 48.7 | 58 | 40 |
| K- 07 40 46 03 | G 1 1/4 | 54.0 | 67 | 49 |
| K- 07 40 46 04 | G 1 1/2 | 58.9 | 76 | 56 |
| K- 07 40 46 05 | G 2 | 62.2 | 90 | 68 |