


K-XV RD 6-KANT

Double nipples, unequal, hexagonal



Darba spiediens
Max. 20 bar
Ārējā vītne
Parallel to DIN EN ISO 228-1
Materiāls
Stainless steel 1.4408

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | L1 mm | L2 mm | SW | Vītne 1 ārpusē | Vītne 2 ārpusē |
|----------------|----------|----------|-------|----------------|----------------|
| K- 07 40 12 27 | 30.4 | 11.0 | 15 mm | G 1/4 | G 1/8 |
| K- 07 40 12 28 | 34.2 | 12.0 | 20 mm | G 3/8 | G 1/8 |
| K- 07 40 12 29 | 35.8 | 12.8 | 20 mm | G 3/8 | G 1/4 |
| K- 07 40 12 30 | 38.0 | 13.0 | 24 mm | G 1/2 | G 1/4 |
| K- 07 40 12 31 | 40.0 | 15.0 | 24 mm | G 1/2 | G 3/8 |
| K- 07 40 12 32 | 41.0 | 16.0 | 27 mm | G 3/4 | G 3/8 |
| K- 07 40 12 33 | 42.9 | 16.0 | 29 mm | G 3/4 | G 1/2 |
| K- 07 40 12 34 | 46.0 | 17.0 | 36 mm | G 1 | G 1/2 |
| K- 07 40 12 35 | 46.0 | 16.5 | 36 mm | G 1 | G 3/4 |
| K- 07 40 12 36 | 50.0 | 17.5 | 45 mm | G 1 1/4 | G 3/4 |
| K- 07 40 12 37 | 51.0 | 18.5 | 45 mm | G 1 1/4 | G 1 |
| K- 07 40 12 38 | 52.0 | 18.5 | 51 mm | G 1 1/2 | G 1 |
| K- 07 40 12 39 | 55.0 | 20.7 | 51 mm | G 1 1/2 | G 1 1/4 |
| K- 07 40 12 40 | 58.0 | 20.0 | 62 mm | G 2 | G 1 |
| K- 07 40 12 41 | 60.0 | 21.5 | 63 mm | G 2 | G 1 1/2 |