


K-L-AGR-K OR DRH VA

Male run tees, conical male thread acc. to ISO 7-1, stainless steel



ieteicamās šļūtenes
PTFE hose
Spiediena diapazons
Max. 25 bar
Temperatūras diapazons
-40 °C to +200 °C (depending on the hose quality and diameter)
Materiāls
Nerūsējošais tērauds 1.4404
Blīvējums
Pure metal

Apraksts

Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | L2 mm | SW1 mm | SW2 mm | šļūtenei |
|----------------|--------|----------|----------|-----------|-----------|--------------|
| K- 07 40 30 51 | R 1/8 | 23.0 | 40.0 | 12 | 10 | 6 mm / 4 mm |
| K- 07 40 30 52 | R 1/8 | 23.0 | 40.0 | 14 | 10 | 8 mm / 6 mm |
| K- 07 40 30 49 | R 1/4 | 23.0 | 44.5 | 12 | 10 | 6 mm / 4 mm |
| K- 07 40 30 50 | R 1/4 | 23.0 | 44.5 | 14 | 10 | 8 mm / 6 mm |
| K- 07 40 30 48 | R 1/4 | 26.0 | 47.5 | 16 | 12 | 10 mm / 8 mm |