



ieteicamās šļūtenes  
PTFE hose  
Spiediena diapazons  
Max. 25 bar  
Temperatūras diapazons  
-40 °C to +200 °C (depending on the hose quality and diameter)  
Materiāls  
Nerūsējošais tērauds 1.4404  
Blīvējums  
Pure metal

## Apraksts

Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	SW1 mm	SW2 mm	šļūtenei
K- 07 40 30 19	R 1/8	26.0	12	10	6 mm / 4 mm
K- 07 40 30 20	R 1/8	26.5	14	13	8 mm / 6 mm
K- 07 40 30 17	R 1/4	29.5	12	14	6 mm / 4 mm
K- 07 40 30 18	R 1/4	30.0	14	14	8 mm / 6 mm
K- 07 40 30 16	R 1/4	32.5	16	14	10 mm / 8 mm
K- 07 40 30 21	R 3/8	33.0	16	17	10 mm / 8 mm