

# K-L-STECKVER AG-K VA

Male elbows conical male thread



Impulsu darba spiediens  
Max. 10 bar  
piemērots caurules materiāls  
PVDF, PTFE, stainless steel, PA, PU  
Spiediens  
Max. 15 bar (depending on pipe quality)  
Standarts  
R thread acc. to ISO 7-1  
Vides temperatūra  
-20 °C to max. +150 °C (depending on pipe quality and diameter)  
Materiāls  
Nerūsējošais tērauds 1.4404  
Blīvējums  
FKM

## Apraksts

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējais Ø
K- 07 40 24 37	R 1/8	17.0	16.0	4 mm
K- 07 40 24 38	R 1/8	20.0	16.0	6 mm
K- 07 40 24 39	R 1/8	21.0	17.0	8 mm
K- 07 40 24 35	R 1/4	20.0	20.0	6 mm
K- 07 40 24 36	R 1/4	21.0	20.0	8 mm
K- 07 40 46 80	R 1/4	25.5	22.5	10 mm