


# K-L-STECKVER DREH AG OR VA

Male elbows, swivel type, parallel male thread with O-ring



Impulsu darba spiediens  
Max. 10 bar  
piemērots caurules materiāls  
PVDF, PTFE, stainless steel, PA, PU  
Spiediens  
Max. 15 bar (depending on pipe quality)  
Standarts  
G-Gewinde nach DIN EN ISO 228-1, mit O-Ring  
Vides temperatūra  
-20 °C to max. +150 °C (depending on pipe quality and diameter)  
Materiāls  
Nerūsējošais tērauds 1.4404  
Blīvējums  
FKM

## Apraksts

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējais Ø	SW
K- 07 40 46 76	M 5	17.0	14.0	4 mm	9 mm
K- 07 40 23 91	G 1/8	17.0	16.0	4 mm	13 mm
K- 07 40 23 93	G 1/8	22.0	18.0	8 mm	13 mm
K- 07 40 23 92	G 1/8	21.5	18.0	6 mm	13 mm
K- 07 40 23 89	G 1/4	21.5	20.0	6 mm	16 mm
K- 07 40 23 90	G 1/4	22.0	20.0	8 mm	16 mm
K- 07 40 23 88	G 1/4	25.5	22.5	10 mm	16 mm
K- 07 40 23 94	G 3/8	25.5	24.0	10 mm	21 mm
K- 07 40 23 95	G 3/8	28.0	26.5	12 mm	21 mm
K- 07 40 23 87	G 1/2	28.0	31.0	12 mm	22 mm