



Darba spiediens
Max. 20 bar
Materiāls
Nerūsējošais tērauds 1.4571

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | L2 mm | uzmavuzgrieznim | šļūtenei | SW |
|----------------|--------|----------|----------|-----------------|----------|-------|
| K- 07 40 49 22 | R 1/4 | 39.7 | 9.7 | LW 9 mm | LW 9 mm | 17 mm |
| K- 07 40 49 31 | R 3/8 | 40.1 | 10.1 | LW 9 mm | LW 9 mm | 19 mm |
| K- 07 40 49 34 | R 3/8 | 43.1 | 10.1 | LW 13 mm | LW 13 mm | 19 mm |
| K- 07 40 49 45 | R 1/2 | 47.2 | 13.2 | LW 13 mm | LW 13 mm | 24 mm |
| K- 07 40 49 46 | R 1/2 | 55.2 | 13.2 | LW 19 mm | LW 19 mm | 24 mm |
| K- 07 40 49 52 | R 3/4 | 56.2 | 14.5 | LW 19 mm | LW 19 mm | 32 mm |
| K- 07 40 49 59 | R 1 | 58.8 | 16.8 | LW 25 mm | LW 25 mm | 38 mm |