

# K-T-STECK VERS DRE AG OR VA

Male branch tees, swivel type, parallel male thread with O-ring



Impulsu darba spiediens  
Max. 10 bar  
piemērots caurules materiāls  
PVDF, PTFE, stainless steel, PA, PU  
Spiediens  
Max. 15 bar (depending on pipe quality)  
Standarts  
G-Gewinde nach DIN EN ISO 228-1, mit O-Ring  
Vides temperatūra  
-20 °C to max. +150 °C (depending on pipe quality and diameter)  
Materiāls  
Nerūsējošais tērauds 1.4404  
Blīvējums  
FKM

## Apraksts

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	šļūtenes ārējais Ø	SW
K- 07 40 46 81	M 5	34.0	18.0	4 mm	9 mm
K- 07 40 24 52	G 1/8	34.0	20.0	4 mm	13 mm
K- 07 40 24 53	G 1/8	42.0	22.5	6 mm	13 mm
K- 07 40 24 54	G 1/8	43.0	22.5	8 mm	13 mm
K- 07 40 24 50	G 1/4	42.0	24.5	6 mm	16 mm
K- 07 40 24 51	G 1/4	43.0	24.5	8 mm	16 mm
K- 07 40 24 49	G 1/4	50.0	25.5	10 mm	16 mm
K- 07 40 24 55	G 3/8	50.0	27.0	10 mm	21 mm