



Ekspluatācijas temperatūra
-20 °C to +70 °C in air; +1 °C to +70 °C in water
Blīvējums
NBR
Materiāls
Acetalpolymerisat (POM)
Darba spiediens
0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)

Apraksts

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Šļūtenes ārējais Ø	L1 mm	L2 mm
K- 07 40 28 63	4 mm	37.1	18.5
K- 07 40 28 64	5 mm	36.9	18.4
K- 07 40 28 65	6 mm	41.0	20.5
K- 07 40 28 66	8 mm	44.0	22.0
K- 07 40 28 67	10 mm	52.6	26.3
K- 07 40 28 68	12 mm	66.4	33.2
K- 07 40 28 69	15 mm	76.8	38.4
K- 07 40 28 70	18 mm	90.6	45.3
K- 07 40 28 71	22 mm	99.3	49.6
K- 07 40 28 72	28 mm	126.2	63.1