



Ekspluatācijas temperatūra
-20 °C to +70 °C in air; +1 °C to +70 °C in water
Blīvējums
NBR
Materiāls
Acetalpolymerisat (POM)
Darba spiediens
0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)

Apraksts

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Īscaurule mm | Šļūtenes ārējais Ø | L1 mm | L2 mm |
|----------------|-----------------|--------------------|----------|----------|
| K- 07 40 29 02 | 4 | 4 mm | 22.8 | 27.3 |
| K- 07 40 29 03 | 5 | 5 mm | 22.8 | 27.3 |
| K- 07 40 29 04 | 6 | 6 mm | 25.9 | 30.8 |
| K- 07 40 29 05 | 8 | 8 mm | 28.4 | 34.4 |
| K- 07 40 29 06 | 10 | 10 mm | 32.7 | 38.8 |
| K- 07 40 29 07 | 12 | 12 mm | 42.3 | 48.5 |
| K- 07 40 29 08 | 15 | 15 mm | 50.7 | 57.9 |
| K- 07 40 29 09 | 18 | 18 mm | 54.2 | 62.1 |