

K-W90 DREH AG OR POM

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVniecība

Male elbows, swivel type, parallel male thread with O-ring (M5 - non-swivel type, w/o O-ring)



Ekspluatācijas temperatūra
-20 °C to +70 °C in air; +1 °C to +70 °C in water
Blīvējums
NBR
Materiāls
Acetalpolymerisat (POM)
Darba spiediens
0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)

Apraksts

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	šļūtenes ārējais Ø	SW	L1 mm	L2 mm
K- 07 40 28 85	G 1/8	6 mm	15 mm	40.0	28.1
K- 07 40 28 86	G 1/8	8 mm	17 mm	45.6	31.1
K- 07 40 28 83	G 1/4	6 mm	17 mm	44.1	28.1
K- 07 40 28 84	G 1/4	8 mm	17 mm	45.5	30.9
K- 07 40 28 82	G 1/4	10 mm	20 mm	50.3	36.2
K- 07 40 28 90	G 3/8	8 mm	22 mm	46.5	30.9
K- 07 40 28 87	G 3/8	10 mm	22 mm	53.3	35.7
K- 07 40 28 88	G 3/8	12 mm	24 mm	60.4	45.0
K- 07 40 28 89	G 3/8	15 mm	22 mm	79.8	51.4
K- 07 40 28 78	G 1/2	10 mm	27 mm	54.8	36.2
K- 07 40 28 79	G 1/2	12 mm	27 mm	63.6	45.5
K- 07 40 28 80	G 1/2	15 mm	27 mm	80.0	50.6
K- 07 40 28 81	G 1/2	18 mm	27 mm	91.5	59.7