

K-W90 VERBINDER POM

Union elbows



Ekspluatācijas temperatūra
-20 °C to +70 °C in air; +1 °C to +70 °C in water
Blīvējums
NBR
Materiāls
Acetalpolymerisat (POM)
Darba spiediens
0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)

Apraksts

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Šļūtenes ārējais Ø | L1 mm | L2 mm |
|----------------|--------------------|----------|----------|
| K- 07 40 28 52 | 4 mm | 25.1 | 25.1 |
| K- 07 40 28 53 | 5 mm | 25.1 | 25.1 |
| K- 07 40 28 54 | 6 mm | 28.1 | 28.1 |
| K- 07 40 28 55 | 8 mm | 30.9 | 30.9 |
| K- 07 40 28 56 | 10 mm | 36.2 | 36.2 |
| K- 07 40 28 57 | 12 mm | 45.0 | 45.0 |
| K- 07 40 28 58 | 15 mm | 51.4 | 51.4 |
| K- 07 40 28 59 | 18 mm | 60.9 | 60.9 |
| K- 07 40 28 60 | 22 mm | 67.4 | 67.4 |
| K- 07 40 28 61 | 28 mm | 87.7 | 87.7 |