

# K-W90 VERBINDER POM

Union elbows



Ekspluatācijas temperatūra  
-20 °C to +70 °C in air; +1 °C to +70 °C in water  
Blīvējums  
NBR  
Materiāls  
Acetalpolymerisat (POM)  
Darba spiediens  
0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)

## Apraksts

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Šļūtenes ārējais Ø	L1 mm	L2 mm
K- 07 40 28 52	4 mm	25.1	25.1
K- 07 40 28 53	5 mm	25.1	25.1
K- 07 40 28 54	6 mm	28.1	28.1
K- 07 40 28 55	8 mm	30.9	30.9
K- 07 40 28 56	10 mm	36.2	36.2
K- 07 40 28 57	12 mm	45.0	45.0
K- 07 40 28 58	15 mm	51.4	51.4
K- 07 40 28 59	18 mm	60.9	60.9
K- 07 40 28 60	22 mm	67.4	67.4
K- 07 40 28 61	28 mm	87.7	87.7