

Male connectors, parallel male thread with O-ring



Ekspluatācijas temperatūra
-20 °C to +70 °C in air; +1 °C to +70 °C in water
Blīvējums
NBR
Materiāls
Acetalpolymerisat (POM)
Darba spiediens
0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)

Apraksts

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Šļūtenes ārējais Ø	SW	L1 mm
K- 07 40 28 31	G 1/8	4 mm	14 mm	22.9
K- 07 40 28 32	G 1/8	5 mm	14 mm	23.0
K- 07 40 28 33	G 1/8	6 mm	15 mm	26.1
K- 07 40 28 34	G 1/8	8 mm	17 mm	26.5
K- 07 40 28 27	G 1/4	4 mm	17 mm	24.9
K- 07 40 28 28	G 1/4	5 mm	17 mm	25.0
K- 07 40 28 29	G 1/4	6 mm	17 mm	24.6
K- 07 40 28 30	G 1/4	8 mm	17 mm	25.0
K- 07 40 28 26	G 1/4	10 mm	20 mm	32.2
K- 07 40 28 38	G 3/8	8 mm	22 mm	26.0
K- 07 40 28 36	G 3/8	10 mm	22 mm	29.2
K- 07 40 28 37	G 3/8	12 mm	24 mm	31.5
K- 07 40 28 22	G 1/2	10 mm	27 mm	29.9
K- 07 40 28 23	G 1/2	12 mm	27 mm	35.0
K- 07 40 28 24	G 1/2	15 mm	27 mm	39.2
K- 07 40 28 25	G 1/2	18 mm	-	55.9
K- 07 40 28 35	G 3/4	22 mm	-	62.0