

# K-T-EINSCHR STUTZEN

Male stud tees, polyamide, conical male thread acc. to ISO 7-1



Temperatūras diapazons  
-40 °C to +90 °C

## Apraksts

Lightweight tube connectors distinguished by high strength, toughness, resistance to abrasion and impact resistance. Resistant to: Acetone, benzene, benzene, butane, alcohols, diesel fuels, crude oil, natural gas, ethanol, fruit juices, glycerine, fuel oil, hydraulic fluids, aliphatic ketones, carbon dioxide, carbonic acid, engine oils, methanol, propane, liquefied gas, lubricating oils, lubricating greases, town gas, washing liquor and water.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	maks. pieļaujamais pārspiediens bar	SW	šļūtenei
K- 07 40 16 79	R 1/8	42.0	18.0	10	10 mm	LW 4 mm
K- 07 40 16 80	R 1/8	57.0	21.0	10	10 mm	LW 6 mm
K- 07 40 16 81	R 1/4	42.0	23.0	10	14 mm	LW 4 mm
K- 07 40 16 82	R 1/4	57.0	26.0	10	14 mm	LW 6 mm
K- 07 40 16 83	R 1/4	66.0	27.5	10	14 mm	LW 8 mm
K- 07 40 46 53	R 3/8	71.0	30.0	10	17 mm	LW 10 mm