


# K-XVM ZYL POM BLAU

Male connectors, parallel male thread



Ekspluatācijas spiediens  
0 - 10 bar  
Temperatūras diapazons  
-10 °C to +60 °C

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | L1<br>mm | SW    | šļūtenei     |
|----------------|--------|----------|-------|--------------|
| K- 07 40 33 15 | G 1/8  | 28.0     | 13 mm | 6 mm / 4 mm  |
| K- 07 40 33 16 | G 1/8  | 29.5     | 13 mm | 8 mm / 6 mm  |
| K- 07 40 33 17 | G 1/4  | 31.0     | 17 mm | 6 mm / 4 mm  |
| K- 07 40 33 18 | G 1/4  | 32.0     | 17 mm | 8 mm / 6 mm  |
| K- 07 40 33 19 | G 1/4  | 37.5     | 19 mm | 12 mm / 9 mm |
| K- 07 40 33 20 | G 1/4  | 34.0     | 17 mm | 10 mm / 8 mm |
| K- 07 40 33 21 | G 3/8  | 34.0     | 19 mm | 8 mm / 6 mm  |
| K- 07 40 33 22 | G 3/8  | 35.5     | 19 mm | 10 mm / 8 mm |
| K- 07 40 33 23 | G 3/8  | 37.5     | 19 mm | 12 mm / 9 mm |