



Ekspluatācijas spiediens
Dependent on operating temperature; Max. 10 bar (at 20 °C); Max. 1 bar (at 60 °C)
Skrūvelements
Polyamide (PA)
Spīlgredzens
Polypropylene (PP)
Uzgrieznis
Polypropylene (PP)

Apraksts

Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis.
Not suitable for use with acids.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | L2 mm | SW | Šļūtenei |
|----------------|--------|----------|----------|-------|--------------|
| K- 07 40 32 30 | G 1/8 | 31.5 | 8.0 | 14 mm | 4 mm / 6 mm |
| K- 07 40 32 31 | G 1/8 | 36.5 | 8.0 | 17 mm | 6 mm / 8 mm |
| K- 07 40 32 32 | G 1/8 | 40.5 | 8.0 | 19 mm | 8 mm / 10 mm |
| K- 07 40 32 33 | G 1/8 | 44.5 | 8.0 | 22 mm | 9 mm / 12 mm |
| K- 07 40 32 34 | G 1/4 | 37.0 | 12.0 | 17 mm | 4 mm / 6 mm |
| K- 07 40 32 35 | G 1/4 | 41.0 | 12.0 | 17 mm | 6 mm / 8 mm |
| K- 07 40 32 36 | G 1/4 | 45.0 | 12.0 | 19 mm | 8 mm / 10 mm |
| K- 07 40 32 37 | G 1/4 | 48.5 | 12.0 | 22 mm | 9 mm / 12 mm |
| K- 07 40 32 38 | G 3/8 | 38.5 | 12.0 | 22 mm | 4 mm / 6 mm |
| K- 07 40 32 39 | G 3/8 | 42.5 | 12.0 | 22 mm | 6 mm / 8 mm |
| K- 07 40 32 40 | G 3/8 | 45.5 | 12.0 | 22 mm | 8 mm / 10 mm |
| K- 07 40 32 41 | G 3/8 | 49.5 | 12.0 | 22 mm | 9 mm / 12 mm |
| K- 07 40 32 42 | G 1/2 | 43.0 | 14.0 | 27 mm | 4 mm / 6 mm |
| K- 07 40 32 43 | G 1/2 | 47.0 | 14.0 | 27 mm | 6 mm / 8 mm |
| K- 07 40 32 44 | G 1/2 | 50.0 | 14.0 | 27 mm | 8 mm / 10 mm |
| K- 07 40 32 45 | G 1/2 | 54.0 | 14.0 | 27 mm | 9 mm / 12 mm |