



Ekspluatācijas spiediens
Dependent on operating temperature; Max. 10 bar (at 20 °C); Max. 1 bar (at 60 °C)
Skrūvelements
Polyamide (PA)
Spīlgredzens
Polypropylene (PP)
Uzgrieznis
Polypropylene (PP)

Apraksts

Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzene, diesel oil, fuel oil and alkalis.
Not suitable for use with acids.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenei
K- 07 40 32 82	G 1/8	25.0	20.0	4 mm / 6 mm
K- 07 40 32 83	G 1/8	30.0	23.0	6 mm / 8 mm
K- 07 40 32 84	G 1/8	36.0	25.0	8 mm / 10 mm
K- 07 40 32 85	G 1/8	40.0	27.0	9 mm / 12 mm
K- 07 40 32 86	G 1/4	26.0	25.0	4 mm / 6 mm
K- 07 40 32 87	G 1/4	30.0	27.0	6 mm / 8 mm
K- 07 40 32 88	G 1/4	36.0	32.0	8 mm / 10 mm
K- 07 40 32 89	G 1/4	40.0	31.0	9 mm / 12 mm
K- 07 40 32 90	G 3/8	29.0	30.0	4 mm / 6 mm
K- 07 40 32 91	G 3/8	33.0	27.0	6 mm / 8 mm
K- 07 40 32 92	G 3/8	36.0	29.0	8 mm / 10 mm
K- 07 40 32 93	G 3/8	40.0	31.0	9 mm / 12 mm
K- 07 40 32 94	G 1/2	32.0	29.0	4 mm / 6 mm
K- 07 40 32 95	G 1/2	36.0	29.0	6 mm / 8 mm
K- 07 40 32 96	G 1/2	39.0	31.0	8 mm / 10 mm
K- 07 40 32 97	G 1/2	43.0	33.0	9 mm / 12 mm