



Ekspluatācijas spiediens  
Dependent on operating temperature; Max. 10 bar (at 20 °C); Max. 1 bar (at 60 °C)  
Skrūvelements  
Polyamide (PA)  
Spīlgredzens  
Polypropylene (PP)  
Uzgrieznis  
Polypropylene (PP)

## Apraksts

Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzene, diesel oil, fuel oil and alkalis. <br>Not suitable for use with acids.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenei
K- 07 40 32 82	G 1/8	25.0	20.0	4 mm / 6 mm
K- 07 40 32 83	G 1/8	30.0	23.0	6 mm / 8 mm
K- 07 40 32 84	G 1/8	36.0	25.0	8 mm / 10 mm
K- 07 40 32 85	G 1/8	40.0	27.0	9 mm / 12 mm
K- 07 40 32 86	G 1/4	26.0	25.0	4 mm / 6 mm
K- 07 40 32 87	G 1/4	30.0	27.0	6 mm / 8 mm
K- 07 40 32 88	G 1/4	36.0	32.0	8 mm / 10 mm
K- 07 40 32 89	G 1/4	40.0	31.0	9 mm / 12 mm
K- 07 40 32 90	G 3/8	29.0	30.0	4 mm / 6 mm
K- 07 40 32 91	G 3/8	33.0	27.0	6 mm / 8 mm
K- 07 40 32 92	G 3/8	36.0	29.0	8 mm / 10 mm
K- 07 40 32 93	G 3/8	40.0	31.0	9 mm / 12 mm
K- 07 40 32 94	G 1/2	32.0	29.0	4 mm / 6 mm
K- 07 40 32 95	G 1/2	36.0	29.0	6 mm / 8 mm
K- 07 40 32 96	G 1/2	39.0	31.0	8 mm / 10 mm
K- 07 40 32 97	G 1/2	43.0	33.0	9 mm / 12 mm