

# K-ABSPV STECK GEW SCH BESCH

Shut-off valves, male thread, plug connection, flow direction to tube, conical thread,  
coated



Darba spiediens  
Max. 15 bar, coarse vacuum  
Darba vides  
Compressed air and all gases or liquids that are compatible with the materials  
ieteicamās šļūtenes  
PU or PA (nylon)  
Pieteikums platība  
Air, vacuum  
Temperatūras diapazons  
-20 °C to +80 °C  
Blīvēšanas virsma  
Parallel version: O-ring in housing, Conical version: thread coating  
Materiāls  
Plastic, Nickel plated brass  
Piespiedējgredzens  
Plastic

## Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vitnes	L1 mm	L2 mm	šļūtenes ārējais Ø	SW
K- 07 40 07 90	R 1/8	58.0	42.6	6 mm	12 mm
K- 07 40 07 91	R 1/8	58.9	42.6	8 mm	14 mm
K- 07 40 07 88	R 1/4	60.5	42.6	6 mm	12 mm
K- 07 40 07 89	R 1/4	60.9	42.6	8 mm	14 mm
K- 07 40 07 86	R 1/4	72.4	47.0	10 mm	17 mm
K- 07 40 07 87	R 1/4	73.3	47.0	12 mm	21 mm
K- 07 40 07 94	R 3/8	62.4	42.6	8 mm	17 mm
K- 07 40 07 92	R 3/8	73.4	47.0	10 mm	17 mm
K- 07 40 07 93	R 3/8	74.3	47.0	12 mm	21 mm
K- 07 40 07 84	R 1/2	76.9	47.0	10 mm	21 mm
K- 07 40 07 85	R 1/2	77.3	47.0	12 mm	21 mm