

# K-L-STECKVER ABSP DREH AG-K

Angle stop valves, swivel type, conical male thread, coated



Darba spiediens  
Max. 10 bar, vacuum  
Darba vides  
Saspiests gaiss  
ieteicamās šļūtenes  
PU or PA (nylon)  
Pieteikums platība  
Air, vacuum  
Standarts  
R-Gewinde nach ISO 7-1, Gewindebeschichtung  
Temperatūras diapazons  
0 °C to +60 °C  
Blīvēšanas virsma  
Conical version: thread coating  
Materiāls  
Plastic, Nickel plated brass  
Piespiedējgredzens  
Plastic

## Apraksts

The air supply is completely shut off as soon as the hose is disconnected from the union. &lt;br&gt;The flow rate is only guaranteed if the hose is securely inserted.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	šļūtenes ārējam Ø	SW
K- 07 40 08 53	R 1/8	29.5	24.5	4 mm	10 mm
K- 07 40 08 54	R 1/8	32.8	26.5	6 mm	12 mm
K- 07 40 08 55	R 1/8	42.9	28	8 mm	14 mm
K- 07 40 08 51	R 1/4	29.4	26.7	6 mm	14 mm
K- 07 40 08 52	R 1/4	33.0	29.5	8 mm	14 mm
K- 07 40 08 50	R 1/4	42.5	34.3	10 mm	17 mm
K- 07 40 08 58	R 3/8	33.0	31.0	8 mm	17 mm
K- 07 40 08 56	R 3/8	42.5	35.3	10 mm	17 mm
K- 07 40 08 57	R 3/8	46.5	37.0	12 mm	21 mm
K- 07 40 08 48	R 1/2	42.5	38.8	10 mm	21 mm
K- 07 40 08 49	R 1/2	46.5	40.0	12 mm	21 mm