


K-SCHOTT-STECKVERB ABSP

Female bulkhead stop unions (pressure max. 10 bar)

HANSA FLEX
OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Darba spiediens
Max. 10 bar, vacuum
Darba vides
Saspiests gaiss
ieteicamās šļūtenes
PU or PA (nylon)
Pieteikums platība
Air, vacuum
Standarts
M thread acc. to DIN 13-1, with O-Ring
G thread acc. to DIN EN ISO 228-1, with O-Ring
R thread acc. to ISO 7-1, thread coating
Temperatūras diapazons
0 °C to +60 °C
Materiāls
Plastic, Nickel plated brass
Piespiedējgredzens
Plastic

Apraksts

The air supply is completely shut off as soon as the hose is disconnected from the union.
The flow rate is only guaranteed if the hose is securely inserted.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	šļūtenes ārējam Ø	SW
K- 07 40 43 74	M 12 x 1.5	41.0	4 mm	14 mm
K- 07 40 43 75	M 14 x 1.5	44.5	6 mm	17 mm
K- 07 40 43 76	M 16 x 1.5	50.3	8 mm	19 mm
K- 07 40 43 77	M 20 x 1.5	58.5	10 mm	24 mm
K- 07 40 43 78	M 24 x 1.5	62.2	12 mm	27 mm