


K-STECKVERSCHR ABSP AGR OR

Straight stop valves, parallel male thread with O-ring



Darba spiediens
Max. 10 bar, vacuum
Darba vides
Saspiests gaiss
ieteicamās šļūtenes
PU or PA (nylon)
Pieteikums platība
Air, vacuum
Standarts
G-Gewinde nach DIN EN ISO 228-1, mit O-Ring
Temperatūras diapazons
0 °C to +60 °C
Blīvēšanas virsma
O-ring (NBR)
Materiāls
Plastic, Nickel plated brass
Piespiedējgredzens
Plastic

Apraksts

The air supply is completely shut off as soon as the hose is disconnected from the union.
The flow rate is only guaranteed if the hose is securely inserted.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	šļūtenes ārējam Ø	SW
K- 07 40 08 18	G 1/8	27.5	4 mm	14 mm
K- 07 40 08 19	G 1/8	27.0	6 mm	14 mm
K- 07 40 08 20	G 1/8	29.0	8 mm	14 mm
K- 07 40 08 16	G 1/4	27.0	6 mm	17 mm
K- 07 40 08 17	G 1/4	31.9	8 mm	17 mm
K- 07 40 08 15	G 1/4	34.9	10 mm	17 mm
K- 07 40 08 23	G 3/8	31.9	8 mm	20 mm
K- 07 40 08 21	G 3/8	37.0	10 mm	20 mm
K- 07 40 08 22	G 3/8	38.0	12 mm	21 mm
K- 07 40 08 13	G 1/2	37.0	10 mm	24 mm
K- 07 40 08 14	G 1/2	38.0	12 mm	24 mm