

# K-XRD STECKANSCHLUSS

Straight non-return valves with plug connection



Darba spiediens  
Max. 10 bar, vacuum  
Darba vides  
Saspiests gaiss  
ieteicamās šļūtenes  
PU or PA (nylon)  
Pieteikums platība  
Air, vacuum  
Temperatūras diapazons  
0 °C to +60 °C  
Blīvēšanas virsma  
O-ring (NBR)  
Materiāls  
Plastic, Nickel plated brass  
Piespiedējgredzens  
Plastic

## Apraksts

The non-return function of these push-in fittings prevents the air from flowing back. the unidirectional design means air flow is only possible in one direction. These valves are available with air flow from the port to the tube or from the tube to the port.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | L1<br>mm | S_kotn_jais spiediens nom.<br>bar | šļūtenes ārējam Ø |
|----------------|----------|-----------------------------------|-------------------|
| K- 07 40 09 02 | 41.9     | 0.2                               | 4 mm              |
| K- 07 40 09 03 | 47.4     | 0.2                               | 6 mm              |
| K- 07 40 09 04 | 51.0     | 0.2                               | 8 mm              |
| K- 07 40 09 05 | 65.2     | 0.2                               | 10 mm             |
| K- 07 40 09 06 | 64.0     | 0.2                               | 12 mm             |