


Male connectors, round, conical male thread, coated with inner hex



Darba spiediens  
Max. 15 bar, coarse vacuum  
Darba vides  
Compressed air and all gases or liquids that are compatible with the materials  
ieteicamās šļūtenes  
PU or PA (nylon)  
Pieteikums platība  
Air, vacuum  
Temperatūras diapazons  
-20 °C to +80 °C  
Blīvēšanas virsma  
Conical version: thread coating  
Materiāls  
Plastic, Nickel plated brass  
Piespiedējgredzens  
Plastic

## Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	Sešstūra iedobe mm	šļūtenes ārējam Ø
K- 07 40 09 38	R 1/8	19.8	3.0	4 mm
K- 07 40 09 39	R 1/8	20.7	4.0	6 mm
K- 07 40 09 40	R 1/8	27.1	5.0	8 mm
K- 07 40 09 37	R 1/8	29.6	5.0	10 mm
K- 07 40 09 34	R 1/4	17.9	3.0	4 mm
K- 07 40 09 35	R 1/4	22.5	4.0	6 mm
K- 07 40 09 36	R 1/4	24.6	5.0	8 mm
K- 07 40 09 33	R 1/4	30.9	6.0	10 mm
K- 07 40 09 44	R 3/8	20.1	4.0	6 mm
K- 07 40 09 45	R 3/8	24.6	6.0	8 mm
K- 07 40 09 41	R 3/8	26.9	8.0	10 mm
K- 07 40 09 42	R 3/8	29.6	8.0	12 mm
K- 07 40 09 43	R 3/8	38.1	8.0	16 mm
K- 07 40 09 31	R 1/2	24.1	4.0	6 mm
K- 07 40 09 32	R 1/2	25.6	6.0	8 mm
K- 07 40 09 28	R 1/2	25.3	8.0	10 mm
K- 07 40 09 29	R 1/2	32.6	8.0	12 mm
K- 07 40 09 30	R 1/2	35.1	10.0	16 mm