

K-T-STECK VERS DRE AG-K BE

Male branch tees, swivel type, conical male thread, coated



Darba spiediens
Max. 15 bar, coarse vacuum

Darba vides
Compressed air and all gases or liquids that are compatible with the materials
ieteicamās šļūtenes
PU or PA (nylon)

Pieteikums platība
Air, vacuum

Temperatūras diapazons
-20 °C to +80 °C

Blīvēšanas virsma
Conical version: thread coating

Materiāls
Plastic, Nickel plated brass

Piespiedējgredzens
Plastic

Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vitnes	L1 mm	L2 mm	šļūtenes ārējam Ø	SW
K- 07 40 02 89	R 1/8	36.0	21.0	4 mm	10 mm
K- 07 40 02 90	R 1/8	40.0	22.1	6 mm	10 mm
K- 07 40 02 91	R 1/8	45.4	26.6	8 mm	10 mm
K- 07 40 02 86	R 1/4	36.0	22.5	4 mm	14 mm
K- 07 40 02 87	R 1/4	40.0	23.6	6 mm	14 mm
K- 07 40 02 88	R 1/4	45.4	25.2	8 mm	14 mm
K- 07 40 02 84	R 1/4	53.8	29.6	10 mm	17 mm
K- 07 40 02 85	R 1/4	58.6	30.9	12 mm	17 mm
K- 07 40 02 95	R 3/8	40.0	25.1	6 mm	17 mm
K- 07 40 02 96	R 3/8	45.4	26.7	8 mm	17 mm
K- 07 40 02 92	R 3/8	53.8	28.1	10 mm	17 mm
K- 07 40 02 93	R 3/8	58.6	29.4	12 mm	17 mm
K- 07 40 02 94	R 3/8	69.0	36.2	16 mm	20 mm
K- 07 40 02 82	R 1/2	40.0	28.1	6 mm	21 mm
K- 07 40 02 83	R 1/2	45.4	29.7	8 mm	21 mm
K- 07 40 02 79	R 1/2	53.8	31.1	10 mm	21 mm
K- 07 40 02 80	R 1/2	58.6	32.4	12 mm	21 mm
K- 07 40 02 81	R 1/2	69.0	39.2	16 mm	21 mm