



Ekspluatācijas spiediens  
Max. 16 bar (at +20 °C)  
Ekspluatācijas temperatūra  
-20 °C to +70 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
NBR, siliconefree  
Piespiedējgredzens  
Hostaform (black nickel-plated for Ø 10, 12)  
Spīlžoklis  
Stainless steel AISI 316

## Apraksts

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējam Ø	SW
K- 07 40 29 65	R 1/8	16.1	17.5	4 mm	10 mm
K- 07 40 29 66	R 1/8	20.0	17.5	6 mm	10 mm
K- 07 40 29 67	R 1/8	24.0	18.5	8 mm	10 mm
K- 07 40 29 63	R 1/4	23.0	22.0	6 mm	12 mm
K- 07 40 29 64	R 1/4	24.0	22.0	8 mm	12 mm
K- 07 40 29 62	R 1/4	24.0	22.0	10 mm	14 mm