

# K-W90 DERH AG 1

Male elbows, swivel type, parallel male thread



Ekspluatācijas spiediens  
Max. 16 bar (at +20 °C)  
Ekspluatācijas temperatūra  
-20 °C to +70 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
NBR, siliconefree  
Piespiedējgredzens  
Hostaform (black nickel-plated for Ø 10, 12)  
Spīļžoklis  
Stainless steel AISI 316

## Apraksts

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	šļūtenes ārējam Ø	SW
K- 07 40 29 68	M 5	19.0	14.5	4 mm	9 mm
K- 07 40 29 69	M 5	21.0	14.5	6 mm	9 mm
K- 07 40 29 76	G 1/8	19.0	20.0	4 mm	13 mm
K- 07 40 29 77	G 1/8	21.0	20.0	6 mm	13 mm
K- 07 40 29 78	G 1/8	24.0	20.0	8 mm	13 mm
K- 07 40 29 73	G 1/4	19.0	24.0	4 mm	13 mm
K- 07 40 29 74	G 1/4	21.0	24.0	6 mm	13 mm
K- 07 40 29 75	G 1/4	24.0	24.0	8 mm	13 mm
K- 07 40 29 72	G 1/4	27.0	24.0	10 mm	16 mm
K- 07 40 29 81	G 3/8	24.0	25.5	8 mm	13 mm
K- 07 40 29 79	G 3/8	27.0	28.0	10 mm	16 mm
K- 07 40 29 80	G 3/8	28.0	28.5	12 mm	20 mm
K- 07 40 29 70	G 1/2	27.0	30.0	10 mm	16 mm
K- 07 40 29 71	G 1/2	28.0	33.5	12 mm	20 mm