

# K-W90 DERH AG 1

Male elbows, swivel type, parallel male thread



Ekspluatācijas spiediens  
Max. 16 bar (at +20 °C)  
Ekspluatācijas temperatūra  
-20 °C to +70 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
NBR, siliconefree  
Piespiedējgredzens  
Hostaform (black nickel-plated for Ø 10, 12)  
Spīlžoklis  
Stainless steel AISI 316

## Apraksts

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | L1<br>mm | L2<br>mm | šļūtenes ārējam Ø | SW    |
|----------------|--------|----------|----------|-------------------|-------|
| K- 07 40 29 68 | M 5    | 19.0     | 14.5     | 4 mm              | 9 mm  |
| K- 07 40 29 69 | M 5    | 21.0     | 14.5     | 6 mm              | 9 mm  |
| K- 07 40 29 76 | G 1/8  | 19.0     | 20.0     | 4 mm              | 13 mm |
| K- 07 40 29 77 | G 1/8  | 21.0     | 20.0     | 6 mm              | 13 mm |
| K- 07 40 29 78 | G 1/8  | 24.0     | 20.0     | 8 mm              | 13 mm |
| K- 07 40 29 73 | G 1/4  | 19.0     | 24.0     | 4 mm              | 13 mm |
| K- 07 40 29 74 | G 1/4  | 21.0     | 24.0     | 6 mm              | 13 mm |
| K- 07 40 29 75 | G 1/4  | 24.0     | 24.0     | 8 mm              | 13 mm |
| K- 07 40 29 72 | G 1/4  | 27.0     | 24.0     | 10 mm             | 16 mm |
| K- 07 40 29 81 | G 3/8  | 24.0     | 25.5     | 8 mm              | 13 mm |
| K- 07 40 29 79 | G 3/8  | 27.0     | 28.0     | 10 mm             | 16 mm |
| K- 07 40 29 80 | G 3/8  | 28.0     | 28.5     | 12 mm             | 20 mm |
| K- 07 40 29 70 | G 1/2  | 27.0     | 30.0     | 10 mm             | 16 mm |
| K- 07 40 29 71 | G 1/2  | 28.0     | 33.5     | 12 mm             | 20 mm |