

K-W90 DERH AG 1

Male elbows, swivel type, parallel male thread



Ekspluatācijas spiediens
Max. 16 bar (at +20 °C)
Ekspluatācijas temperatūra
-20 °C to +70 °C
Materiāls
Niķelēts misiņš
Blīvgredzens
NBR, siliconefree
Piespiedējgredzens
Hostaform (black nickel-plated for Ø 10, 12)
Spīļžoklis
Stainless steel AISI 316

Apraksts

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | L2 mm | šļūtenes ārējam Ø | SW |
|----------------|--------|----------|----------|-------------------|-------|
| K- 07 40 29 68 | M 5 | 19.0 | 14.5 | 4 mm | 9 mm |
| K- 07 40 29 69 | M 5 | 21.0 | 14.5 | 6 mm | 9 mm |
| K- 07 40 29 76 | G 1/8 | 19.0 | 20.0 | 4 mm | 13 mm |
| K- 07 40 29 77 | G 1/8 | 21.0 | 20.0 | 6 mm | 13 mm |
| K- 07 40 29 78 | G 1/8 | 24.0 | 20.0 | 8 mm | 13 mm |
| K- 07 40 29 73 | G 1/4 | 19.0 | 24.0 | 4 mm | 13 mm |
| K- 07 40 29 74 | G 1/4 | 21.0 | 24.0 | 6 mm | 13 mm |
| K- 07 40 29 75 | G 1/4 | 24.0 | 24.0 | 8 mm | 13 mm |
| K- 07 40 29 72 | G 1/4 | 27.0 | 24.0 | 10 mm | 16 mm |
| K- 07 40 29 81 | G 3/8 | 24.0 | 25.5 | 8 mm | 13 mm |
| K- 07 40 29 79 | G 3/8 | 27.0 | 28.0 | 10 mm | 16 mm |
| K- 07 40 29 80 | G 3/8 | 28.0 | 28.5 | 12 mm | 20 mm |
| K- 07 40 29 70 | G 1/2 | 27.0 | 30.0 | 10 mm | 16 mm |
| K- 07 40 29 71 | G 1/2 | 28.0 | 33.5 | 12 mm | 20 mm |