



Darba spiediens
10 bar
Vides temperatūra
Max. +90 °C
Vielas temperatūra
max. +90 °C
Materiāls
Brass with a bare metal surface

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītne 1 | Vītne 2 | L1 mm | L2 mm | L3 mm | SW |
|----------------|---------|---------|----------|----------|----------|-------|
| K- 07 40 44 60 | R 1/8 | R 1/8 | 21.0 | 8.0 | 8.0 | 10 mm |
| K- 07 40 44 61 | R 1/8 | R 1/4 | 24.5 | 8.0 | 11.5 | 14 mm |
| K- 07 40 44 62 | R 1/8 | R 3/8 | 26.0 | 8.0 | 13.0 | 17 mm |
| K- 07 40 00 26 | R 1/4 | R 1/4 | 30.0 | 12.0 | 12.0 | 14 mm |
| K- 07 40 44 66 | R 1/4 | R 3/8 | 29.5 | 11.5 | 13.0 | 17 mm |
| K- 07 40 44 67 | R 1/4 | R 1/2 | 32.5 | 11.5 | 15.5 | 22 mm |
| K- 07 40 00 27 | R 3/8 | R 3/8 | 38.0 | 16.0 | 16.0 | 22 mm |
| K- 07 40 44 70 | R 3/8 | R 1/2 | 34.0 | 15.5 | 13.0 | 22 mm |
| K- 07 40 44 71 | R 3/8 | R 3/4 | 36.5 | 13.0 | 17.5 | 27 mm |
| K- 07 40 00 28 | R 1/2 | R 1/2 | 38.0 | 16.0 | 16.0 | 27 mm |
| K- 07 40 44 74 | R 1/2 | R 3/4 | 39.0 | 17.5 | 15.5 | 27 mm |
| K- 07 40 44 75 | R 1/2 | R 1 | 42.5 | 20.0 | 15.5 | 34 mm |
| K- 07 40 00 29 | R 3/4 | R 3/4 | 51.5 | 22.0 | 22.0 | 32 mm |
| K- 07 40 44 78 | R 3/4 | R 1 | 44.5 | 20.0 | 17.5 | 34 mm |
| K- 07 40 00 30 | R 1 | R 1 | 47.0 | 19.5 | 19.5 | 41 mm |